

## LEED DATA SHEET

DATE:	
PROJECT NAME:	
PROJECT LOCATION:	
NAME OF PRODUCT:	BURmastic ® Adhesive
DESCRIPTION:	Cold Applied Adhesive For Use With BURmastic Ply Sheets
PRODUCT/MATERIAL COST: \$	

### SOLAR REFLECTIVITY INDEX (SRI)

PAVING & SLOPED ROOF >2:12 MUST BE AT LEAST 29:	N/A
LOW SLOPED ROOF MATERIALS MUST BE AT LEAST 78:	N/A

### RECYCLED CONTENT

PRE-CONSUMER:	0	%
POST CONSUMER:	0	%

### REGIONAL QUALIFICATIONS FOR PRODUCT/MATERIALS:

		DISTANCE FROM PROJECT:		MILES
LOCATION OF PROCESS:		DISTANCE FROM PROJECT:		MILES
LOCATION OF MANUFACTURE:	Cleveland, OH	DISTANCE FROM PROJECT:		MILES

### LOW EMITTING MATERIALS:

COATING VOC (GRAMS/L)	SEALANT VOC (GRAMS/L)	ADHESIVE VOC (GRAMS/L)	USE OF MATERIAL
		396 g/L	

### RAPIDLY RENEWABLE MATERIAL:

PERCENT RENEWABLE:	0	%
COST:	\$	

PREPARED BY:	
--------------	--

*\*Extraction/Process/Manufacture is defined as the assembly of a final product not including on-site assembly or installation.  
 \*\*Due to several sources of raw materials for this product, specifying the origin of the component materials may not be possible.*