

Revision Date: 07/29/2015

SAFETY DATA SHEET

1. Identification

Material name: PREMIUM III ASPHALT - PAK FREE

Material: 372000B501

Recommended use and restriction on use

Recommended use: Adhesive Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S. Roofing 3735 Green Road Cleveland OH 44122

US

Contact person:EH&S DepartmentTelephone:216-292-5000

Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Carcinogenicity Category 1B

Unknown toxicity - Health

Acute toxicity, oral 1.5 %
Acute toxicity, dermal 1.5 %
Acute toxicity, inhalation, vapor 100 %
Acute toxicity, inhalation, dust or mist 100 %

Environmental Hazards

Acute hazards to the aquatic Category 3 environment

Unknown toxicity - Environment

Acute hazards to the aquatic 97.9 % environment Chronic hazards to the aquatic environment 100 %

Label Elements

Hazard Symbol:



Signal Word: Danger



Revision Date: 07/29/2015

Hazard Statement: May cause cancer.

Harmful to aquatic life.

Precautionary Statement:

Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Use personal protective

equipment as required.

Response: If exposed or concerned: Get medical advice/attention.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Oxidized asphalt	64742-93-4	60 - 100%
Sulfur	7704-34-9	1 - 5%
Hydrogen sulfide	7783-06-4	0.1 - 1%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact: Wash skin thoroughly with soap and water. If skin irritation occurs: Get

medical advice/attention.

Eye contact: Any material that contacts the eye should be washed out immediately with

water. If easy to do, remove contact lenses. If eye irritation persists: Get

medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.



Revision Date: 07/29/2015

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

6. Accidental release measures

Personal precautions,

protective equipment and emergency procedures:

No data available.

Methods and material for containment and cleaning

up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling:

Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in

case of handling which causes formation of dust.

Conditions for safe storage,

including any incompatibilities: Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Apadona Exposare Eninte					
Chemical Identity	type	Exposure Limit Values	Source		



Revision Date: 07/29/2015

Hydrogen sulfide	TWA	1 ppm	US. ACGIH Threshold Limit Values
			(2011)
	STEL	5 ppm	US. ACGIH Threshold Limit Values
	0.22		(2011)
	Ceiling	20 ppm	US. OSHA Table Z-2 (29 CFR
	Johnnig		1910.1000) (02 2006)
	MAX.	50 ppm	US. OSHA Table Z-2 (29 CFR
	CONC		1910.1000) (02 2006)

Appropriate Engineering

Controls

Mechanical ventilation or local exhaust ventilation may be required.

Observe good industrial hygiene practices. Observe occupational exposure

limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information: Good general ventilation (typically 10 air changes per hour) should be used.

Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists,

mechanical generation of dusts, drying of solids, etc.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear suitable protective clothing.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product.

9. Physical and chemical properties

Appearance

Physical state: solid
Form: solid
Color: Black
Odor: Aromatic

Odor threshold:

pH:

No data available.

No data available.

Melting point/freezing point:

No data available.

No data available.

No data available.

No data available.

Flash Point: > 260 °C > 500 °F(Cleveland Open Cup)

Evaporation rate: Slower than Ether

Flammability (solid, gas): No Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): No data available.
Flammability limit - lower (%): No data available.



Revision Date: 07/29/2015

Explosive limit - upper (%):

Explosive limit - lower (%):

Vapor pressure:

No data available.

No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 0.96

Solubility(ies)

Solubility in water:
Solubility (other):
No data available.
Partition coefficient (n-octanol/water):
No data available.
No data available.
No data available.
Pecomposition temperature:
No data available.
Viscosity:
No data available.

Other information

Minimum ignition temperature: > 343 °C > 650 °F

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of Hazardous

Reactions:

No data available.

Conditions to Avoid: Avoid heat or contamination.

Incompatible Materials: Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and

chromates).

Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

Skin Contact: May be harmful in contact with skin. Causes mild skin irritation.

Eye contact: Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: No data available.



Revision Date: 07/29/2015

Dermal

Product: ATEmix: 2,030.48 mg/kg

Inhalation

Product: No data available.

Specified substance(s):

Oxidized asphalt LC 50 (Rat): > 94.4 mg/m3

Sulfur LC 50 (Rat, 4 h): > 9.23 mg/l

Hydrogen sulfide LC 50 (Rat, 4 h): 444 ppm

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Oxidized asphalt in vivo (Rabbit, 24 hrs): Not irritating

Sulfur in vivo (Rabbit, 24 - 72 hrs): Not irritating

Hydrogen sulfide Irritating

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified



Revision Date: 07/29/2015

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product:
No data available.

riodati. No data avallable.

Specific Target Organ Toxicity - Repeated Exposure
Product:
No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Sulfur LC 50 (Western mosquitofish (Gambusia affinis), 96 h): > 10,000 mg/l

Mortality

Hydrogen sulfide LC 50 (Fathead minnow (Pimephales promelas), 96 h): 0.013 - 0.0172 mg/l

Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Hydrogen sulfide LC 50 (Sand shrimp (Metapenaeus monoceros), 96 h): 0.0352 mg/l Mortality

EC 50 (Oligochaete (Stylaria lacustris)): +/- +/- 50 mg/l Intoxication EC 50 (Leech (Herpobdella octoculata)): +/- +/- 10 mg/l Intoxication EC 50 (Oligochaete (Stylaria lacustris)): +/- +/- 10 mg/l Intoxication EC 50 (Tubificid worm (Tubifex tubifex)): +/- +/- 50 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish



Revision Date: 07/29/2015

Product: No data available.

Specified substance(s):

Oxidized asphalt LL 50 (Oncorhynchus mykiss, 28 d): > 1,000 mg/l QSAR

Sulfur NOAEL (Oncorhynchus mykiss, 28 d): 9.3 mg/l experimental result

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product:
No data available.

Mobility in Soil: No data available.

Other Adverse Effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated



Revision Date: 07/29/2015

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u> Lead and compounds

OSHA hazard(s)
Kidney

(inorganic) Acute toxicity

Central nervous system

Blood

Reproductive toxicity

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Hydrogen sulfide	100 lbs.
Indeno[1,2,3-cd]pyrene	100 lbs.
Benzo(b)fluoranthene/benzo[e]acefenantrileno	1 lbs.
Benzo(k)fluoranthene	5000 lbs.
Chrysene	100 lbs.
Benzo(a)pyrene	1 lbs.
Dibenz(a,h)anthracene	1 lbs.
Benzo(a)anthracene	10 lbs.
Lead and compounds (inorganic)	10 lbs.
Nickel	100 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

Reportable

Chemical IdentityquantityThreshold Planning QuantityHydrogen sulfide100 lbs.500 lbs.



Revision Date: 07/29/2015

SARA 304 Emergency Release Notification

<u>Chemical Identity</u> <u>Reportable quantity</u>

Hydrogen sulfide 100 lbs. 100 lbs. Indeno[1,2,3-cd]pyrene Benzo(b)fluoranthene/benzo[e]acefenantrileno 1 lbs. Benzo(k)fluoranthene 5000 lbs. 100 lbs. Chrysene Benzo(a)pyrene 1 lbs. Dibenz(a,h)anthracene 1 lbs. Benzo(a)anthracene 10 lbs. Lead and compounds (inorganic) 10 lbs. Nickel 100 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity Threshold Planning Quantity

Hydrogen sulfide 500lbs
Oxidized asphalt 500 lbs
Sulfur 500 lbs

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Chemical Identity Reportable quantity

Hydrogen sulfide 10000 lbs

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Oxidized asphalt

Sulfur

US. Massachusetts RTK - Substance List

Chemical Identity

Sulfur

Hydrogen sulfide

Indeno[1,2,3-cd]pyrene

Benzo(b)fluoranthene/benzo[e]acefenantrileno

Benzo(k)fluoranthene

Chrysene

Benzo(a)pyrene

Dibenz(a,h)anthracene

Benzo(a)anthracene

Nickel



Revision Date: 07/29/2015

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Oxidized asphalt

Sulfur

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

Other Regulations:

Regulatory VOC (less water

1 g/l

and exempt solvent):

0.10 %

VOC Method 310:

Inventory Status:

Australia AICS: One or more components in this product are

not listed on or exempt from the Inventory.

Canada DSL Inventory List:

One or more components in this product are

not listed on or exempt from the Inventory.

EINECS, ELINCS or NLP: One or more components in this product are

not listed on or exempt from the Inventory.

Japan (ENCS) List: One or more components in this product are

not listed on or exempt from the Inventory.

China Inv. Existing Chemical Substances: One or more components in this product are

not listed on or exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI): One or more components in this product are

not listed on or exempt from the Inventory.

Canada NDSL Inventory: One or more components in this product are

not listed on or exempt from the Inventory.

Philippines PICCS: One or more components in this product are

not listed on or exempt from the Inventory.

US TSCA Inventory:

One or more components in this product are

not listed on or exempt from the Inventory.

New Zealand Inventory of Chemicals:

One or more components in this product are

not listed on or exempt from the Inventory.

Japan ISHL Listing:

One or more components in this product are

not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are

not listed on or exempt from the Inventory.



Revision Date: 07/29/2015

16.Other information, including date of preparation or last revision

Revision Date: 07/29/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.