PRODUCT DATA SHEET






Part of Tremco Construction Products Group

Building the World to Last

DYNAROUND RG (ROOF GUARD) SLIMLINE™



Fibergrate's new ballasted rooftop guardrail system, DynaRound RG Slimline™, provides safety and fall protection on rooftop applications. While our RG system utilizes counter balance bases, the Slimline systems uses both counterbalance bases in addition to circular galvanized bases with less interference. Similar to our DynaRound RG system, each Slimline system is made of durable, weather-resistant fiberglass reinforced plastic (FRP) composite uprights and rails, galvanized steel base weights, and galvanized connector components. This system meets applicable safety standards in the U.S. and Canada to protect people working at heights.



DynaRound RG Slimline provides the utmost in safety by protecting against injuries or death from accidental falls from the roof. The weighted base system means there is no drilling into the roof to attach the system. This eliminates any damage to the roof that could result from the drilling, including potential sources of leaks.

BENEFITS



Lightweight: Fibergrate FRP products lessen impact on rooftop installations, reduce installation time, can eliminate the need for heavy lifting equipment, and reduce shipping costs.



Long Service Life: Fiberglass products provide outstanding durability and corrosion resistance in demanding applications, providing improved product life over traditional materials.



UV Resistant: UV Inhibitors in the resin matrix, along with a synthetic surfacing veil, provide optimum protection from the effect of UV weathering. In addition, the FRP rails, posts, and outriggers have an additional UV coating suitable for intense UV exposure.



Low Install Cost: Prefabricated FRP components and connectors using set screws for assembly eliminate drilling and almost all field cutting for a rapid. clean installation.



Corrosion Resistant: Fibergrate® fiberglass products are known for their ability to provide corrosion resistance in the harshest environments.



Low Maintenance: The corrosion resistant properties of FRP are easy to clean and reduce or eliminate the need for sandblasting, scraping and painting.

SPECIFICATIONS

Safety Ratings

OSHA Requirements:

- 1926.501(b)(1) 1910.28(b)(1)
- 1926.502(b) 1910.29(b)
- **CAL/OSHA Requirements:**
- 32103212
- 16203209

IBC 2018 Requirements:

- 1015.3
- 1607.8.1 (Modified system required)
- 1015.4.4 • 1015.7
- 1607.8.1.1 • 1607.8.1.2
- **National Building Code of Canada 2015**
- 4.1.5.14
- 9.8.8.2

OH&S

R.R.O. 1990, Reg. 851, s. 13 & 14

Materials of Construction

Rails, posts, and outriggers:

 VEFR (Vinyl ester resin system with a flame spread of 25 or less for dependable resistance to both acidic and alkaline environments)

Fittings and Base Weights:

- Galvanized, cast iron connectors with set screws
- Protective, durable rubber pads on parts that contact roof surface

Size

• 1.9" O.D. Pultruded Round Tube

Colors

Yellow with UV Coating


Light Gray with UV Coating






PRODUCT DATA SHEET

SYSTEM COMPONENTS




TYPICAL SPACING FOR ASSEMBLIES

RETURN CONDITION



KICKER ASSEMBLY

(A kicker assembly can be used as an alternative to the standard "F" outrigger.)



All assembly details can be found on the next page.

Phone: 800-852-6013 | Email: SafetySolutions@tremcoinc.com | www.tremcoroofing.com

Product data sheet

ASSEMBLY DETAILS

DynaRound SL Post Assembly, Yellow ITEM #5041000

Weight = 97 lbs

DESCRIPTION	QTY	PN#
DynaRound SL Post - YL	1	5041610
Open Cross Over	2	793201
Lock Pin	1	793108.2
DynaRound SL Base	1	793108.9

DynaRound SL Post Assembly, LT GRAY ITEM #5041002

Weight = 97 lbs

_		
DESCRIPTION	QTY	PN#
DynaRound SL Post - GR	1	5041612
Open Cross Over	2	793201
Lock Pin	1	793108.2
DynaRound SL Base	1	793108.9

DynaRound SL Kicker Assembly, Yellow ITEM #5041100

Weight = 110 lbs

DESCRIPTION	QTY	PN#
DynaRound SL Post - YL	1	5041610
Open Cross Over	2	793201
Lock Pin	1	793108.2
DynaRound SL Base	1	793108.9
Two Way Elbow	2	793125
Dynaround SL Kicker Rail - YL	2	5041710

DynaRound SL Kicker Assembly, LT GRAY ITEM #5041102

QTY	PN#
1	5041612
2	793201
1	793108.2
1	793108.9
2	793125
2	5041712
	1 2 1 1 2

Through Hole	
PN#	79312
TWO W	AY ELB

End Cap UV Coated Ø1.9" Round

Tube

UV Coated


Ø7/16" Drill

PN #793201 **OPEN CROSS OVER**



ISOMETRIC VIEW

PN #793207 **SPECIAL HOOK***



*Shown upside down

PN #793108.2 **LOCK PIN**

DynaRound SL 'F' Outrigger Assy, Yellow ITEM #5041200

Weight = 148 lbs

•		
DESCRIPTION	QTY	PN#
DynaRound RG Post - YL	1	5040010
Open Cross Over	2	793201
Slipper	1	793206
Roof	3	793208
Special Hook	2	793207
F Outrigger (L = 70") - YL	1	5046110

DynaRound SL'F' Outrigger Assy, LT GRAY ITEM #5041202

Weight = 148 lbs

DESCRIPTION	QTY	PN#
DynaRound RG Post - LG	1	5040012
Open Cross Over	2	793201
Slipper	1	793206
Roof	3	793208
Special Hook	2	793207
F Outrigger (L = 70") - LG	1	5046112


ow

4"

PN # 5041610/5041612


DYNAROUND SL POST

(LENGTH =41-1/4")



ISOMETRIC VIEW

PN #793206 **SLIPPER**



ISOMETRIC VIEW PN #5045110

RETURN (Length = 21-1/16")

PN #793126

SWIVEL ELBOW

ISOMETRIC VIEW

1.9"Ø Round Tube

UV Coated

PN #793131 **BASE FLANGE**

ISOMETRIC VIEW



ISOMETRIC VIEW

PN #793149 **SLEEVE JOINT**



ISOMETRIC VIEW

Swivel Elbow Assembly ITEM #504802

Weight = 4 lbs

Weight = 3 lbs

Weight = 6 lbs

DESCRIPTION

Sleeve Joint

DESCRIPTION

Return (Length: 21-1/16")

Two Way Elbow

DESCRIPTION	QTY	PN#
Swivel Elbow	2	793126

RAIL SPLICE ASSEMBLY

ITEM #504701

RETURN ASSEMBLY, Yellow

ITEM #5045010

2

2

793149

5045110

793125

WALL ASSEMBLY ITEM #504601

Weiaht = 4 lb

Weight - +103		
DESCRIPTION	QTY	PN#
Base Flange	2	793131


90° SPLICE ASSEMBLY ITEM #504801

Weight = 4 lbs		
DESCRIPTION	QTY	PN#
Two Way Elbow	2	793125


RETURN ASSEMBLY, LT GRAY TEM #5045012 = 6 lbs

vveignt = 6 ibs		
DESCRIPTION	QTY	PN#
Return (Length: 21-1/16")	1	5045112
Two Way Elbow	2	793125


PN #793208 **ROOF WEIGHT**



PN #793108.9 **DynaRound SL Base**



Diameter=24"



PN #5046110/5046112 **FOUTRIGGER** (LENGTH=66")

Ø1.9" Round Tube - UV Coated

